

# TECHNICAL SPECIFICATION

## Overview.

| Servicing  |  |                |
|--|--|----------------|
| Service interval   | 25,000 miles                                       |                |
| Motor and battery  |  |                |
| Driven wheels  | Rear   |                |
| Peak power   | 110 kW / 150 PS                                    |                |
| Peak torque  | 255 NM   |                |
| Max. rpm   | 11,500   |                |
| Battery type   | 3 string lithium-ion 400 V                         |                |
| Gross storage capacity                                       | 31 kWh   |                |
| On-board charging (AC/DC)                                    | 22 kW AC / 50 kW DC                                |                |
| Range-extender   |  |                |
| Fuel type  | Petrol   |                |
| Configuration  | Inline 3 DOHC 12-valves                            |                |
| Induction  | Direct injection, turbo-charged                    |                |
| Cubic capacity   | 1,477 cc   |                |
| Power  | 60 kW / 82 PS                                      |                |
| Torque   | 255 NM   |                |
| Fuel tank capacity   | 36 L   |                |
| Performance and economy                                      |  |                |
| 0 - 62 mph   | 13.2 secs  |                |
| Max. speed   | 80 mph   |                |
|  | <b>NEDC</b>  | <b>WLTP*</b>   |
| Official combined fuel economy (mpg)                         | 282.5  | 313.9          |
| Official CO <sub>2</sub> emissions (g/km)                    | 24   | 20             |
| Pure EV (electric-only) range (miles)                        | 81.4**   | 64.5**         |
| Pure EV range City (miles)                                   | N/A  | 78.7**         |
| Total range (miles)  | 425***   | 303 (317 City) |
| Range-extender fuel economy (mpg)                            | 43.5   | 30.1           |
| Brakes   |  |                |
| Braking system   | Front and rear floating caliper / ventilated discs |                |
| ABS, Electronic Stability Control and Emergency Brake Assist |  |                |

\* For more information on the new WLTP emissions test, please visit [www.levc.com/emissions](http://www.levc.com/emissions) \*\* The NEDC and WLTP test must consider the worst case operating scenario and therefore do not include any benefit from regenerative braking \*\*\* 81 miles electric-only range, plus 344 miles range-extended (36 litres at 43.5 mpg)

| Wheels                         |  |
|--------------------------------|--|
| Wheel size                     | 17 x 7J  |
| Tyre size                      | 215/65/R17 103H  |
| Steering                       |  |
| Power steering type            | Electro-hydraulic  |
| Steering ratio                 | 15.2:01  |
| Turning circle (wall-to-wall)  | 8,450 mm   |
| Dimensions (mm)                |  |
| Refer to diagrams overleaf.    |  |
| Access (mm)                    |  |
| Nearside door opening:         |  |
| Max. width / min. width        | 857 / 842  |
| Height                         | 1,319  |
| Sill height                    | 370  |
| Folding step height            | 177  |
| Folding step depth             | 252  |
| Ramp length / extension        | 1,280 / 1,061  |
| Approx. ramp angle (floor)     | 15 degrees   |
| Approx. ramp angle (kerb)      | 11 degrees   |
| Ramp width (between rails)     | 714  |
| Weights (kg)                   |  |
| Kerb weight*                   | 2,230  |
| Mass in running order**        | 2,305  |
| Max. payload***                | 600  |
| Gross Vehicle Weight (GVW)**** | 2,900  |
| Ramp safe working load         | 250  |
| Folding step safe working load | 150  |
| Suspension type                |  |
| Front suspension               | Dual-axis Macpherson strut / anti-roll bar                     |
| Rear suspension                | Double-insulated, 5-link with transverse composite leaf spring |
| Luggage space                  |  |
| Luggage capacity               | 440 L  |

\* The kerb weight refers to the vehicle in running order (with standard equipment) without the driver, passengers or load but with the fuel tank 90% full \*\* The mass in running order includes the kerb weight plus a driver at 75 kg \*\*\* The payload includes the weight of the driver and passengers, luggage and all accessories \*\*\*\* The maximum permitted weight of the vehicle; including driver, passengers, luggage and accessories.

# TECHNICAL SPECIFICATION

Dimensions.



